




Note: The product images shown may change over time as products are updated.

Dimensions



Part Number

CCM1-1808G-I3U2

Features

- Capacitive sensors for the reliable detection of liquids, plastics, powders, pellets and pastes
- Available in plastic or stainless steel housings
- Connectable with a pre-wired cable of any length or with a quick-connector
- Available with PNP, NPN, AC or AC/DC output functions
- Mountable with a shielded or unshielded construction with adjustable sensitivity

Connection

Technical Data

| | |
|----------------------------|---------------------|
| Sensing Type | Capacitive Sensor |
| Body Style | Cylindrical |
| Sensor Housing Material | Chrome Plated Brass |
| Sensor Face Material | PBT |
| Mounting Style | Shielded |
| Diameter | 18 mm |
| Sensing Range: | 8 mm |
| Output Type: | Analog |
| Output Function | Current output |
| Connection | Pre-Wired Cable |
| Body Length | - |
| Operating Voltage | 18-30 VDC |
| Switching Frequency | |
| Operating Temperature | -25 °C - +70 °C |
| Overload Trip Point | |
| Hysteresis: | |
| IP Rating: | |
| Shock Rating: | |
| Short Circuit Protected | YES |
| Reverse Polarity Protected | YES |
| Connector Type | N_A |
| Current Consumption | — |

