



Note: The product images shown may change over time as products are updated.

**Part Number**

**HPPA-12-25-06-L**

**Features**

Inductive Proximity Sensors are used in a wide variety of manufacturing operations where a metal target needs to be sensed. HTM Sensors inductive proximity sensors have a Lifetime Warranty, a CSA or UL approval, and a huge inventory for same-day shipping. For tougher applications where the sensors need more range to stay out of harm's way, or to withstand high temperatures, weld spatter, chemical exposure, oil or other rough environments, HTM Sensors has the widest range of proximity sensors on the market.

**Connection**



**Dimensions**

Body Length (mm)

-

**Technical Data**

Body Style	Cylindrical
Sensor Housing Material	-
Sensor Face Material	PBT Plastic
Mounting Style	-
Diameter	-
Sensing Range:	-
Output Type:	-
Output Function	-
Connection	-
Connector Type	-
Operating Voltage	-
Switching Frequency	-
Operating Temperature	-
Current Consumption	-
IP Rating:	IP67
EMC Rating	RFI>3V/m / EFT>1kV / ESD>4Kv (contact)
Shock Rating:	IEC 60497-5-2 Part 7.4.1&7.4.2
Short Circuit Protected	-
Reverse Polarity Protected	-
Max Current	-
Leakage Current	-
Surge Current	-
Response Time	-
Hysteresis	<15%(Sr)
Overload Trip Point	-
Weld Field Immune	-
Weld Spatter Resistant	-
Body Length (mm)	-



In the USA: 1889 Maryland Ave., Niagara Falls, NY 14305  
 In Canada: 3419 Mainway, Burlington, ON L7M 1A9  
 Toll Free: 1-800-644-1756 • Fax: 888-283-2127  
 service@htmsensors.com